


<b>Manufacturing date</b>	<b>27.6.2008 -</b>
<b>ATEX &amp; IECEx marking</b>	 Ex II 2 G Ex e d IIC T4 Gb or Ex II 2 G Ex mb IIC T4 Gb Ex II 2 D Ex tb IIIC T70°C Db
<b>Product description</b>	Explosion protected portable transformer
<b>Temperature classification</b>	T4 (internal) T70°C (external)
<b>Operating temperature</b>	-20°C ... +40°C
<b>Supply Voltage (min-max)</b>	110V, 230V +/- 6%
<b>Supply Current typical</b>	2A or 4A
<b>Output voltage</b>	12VAC, 24VAC or 48VAC
<b>Output current</b>	Max. 16A
<b>Number of outputs</b>	2 or 4
<b>Electrical class</b>	Class I
<b>Maximum load</b>	42VAC 384W 24VAC 384W 12VAC 192W
<b>Cable</b>	H07BQ-F
<b>Plug and socket options</b>	ATX, CEAG, Marechal, Stahl
<b>Enclosure</b>	Green elastomer, aluminium
<b>Ingress protection</b>	IP66
<b>Weight (without cable, plug and sockets)</b>	18,5kg
<b>Warranty</b>	You will find detailed warranty conditions from <a href="http://www.atexor.com/downloads/warranty">www.atexor.com/downloads/warranty</a>

	Dimensions / mm		
	L	W	H
<b>SLAM® Trans 400EX</b>	534	356	313

