


<b>ATEXOR code</b>	<b>SFN1LED....</b>
<b>Product description</b>	Explosion protected luminary for fixed use
<b>ATEX and IECEx marking</b>	 Ex II 2 G Ex eb mb op is IIC T4 Gb Ex II 2 D Ex tb op is IIIC T90°C Db
<b>Temperature classification</b>	T4 (internal) T90 °C (external)
<b>Operating temperature</b>	-40°C ... +55°C
<b>Light source</b>	1 Led module with SafeEye® technology
<b>Light emitted at source</b>	2825 lm
<b>Luminous flux (measured)</b>	1595 lm
<b>Colour temperature</b>	4600 - 5700 K
<b>Colour rendering index</b>	>80
<b>Photobiological safety</b>	Exempt group (No marking required, safe in normal use)
<b>Supply Voltage</b>	230VAC/DC +/- 6%, 50/60Hz
<b>Supply Current (typical)</b>	230V~0,2 A
<b>Electrical class</b>	Class 1 (230 VAC)
<b>Power</b>	< 25 W
<b>Cable</b>	MCMK 2x2,5/2,5 or equivalent for fixed use
<b>Plug and socket</b>	Not applicable
<b>Enclosure</b>	Dissipative materials (PC & TPE)
<b>Ingress protection</b>	IP66
<b>Weight (without cable and fixings)</b>	1,8 kg
<b>Accessories</b>	70905 ceiling fixing 70904 pole fixing



	Dimensions / mm	
<b>Product model</b>	L	Ø
<b>SLAM® FIXED Novo 1LED</b>	<b>581</b>	<b>112</b>

